

SAFETY DATA SHEET

Polish, wax and dirt remover

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Product name : **Polish, wax and dirt remover**
Product Use Intensive (deep) cleaning removes polish, wax, stubborn dirt and oils from quarry tiles and non calcareous natural stone

Company/undertaking identification

Manufacturer : HG International b.v. **Telephone No.:** : +31 (0)36 54 94 700
Address : Damsluisweg 70 **Fax** : +31 (0)36 54 94 744
 1332 EJ Almere **Internet:** : www.hginternational.com
Country : The Netherlands
Importer : HG UK
Address : Unit 11 Grange Way Business Park Whitehall Road Industrial Estate
 Uk Colchester Essex CO2 8HF
Telephone No.: : +44.1206.795.200
Fax : +44.1206.795.201
Country : United Kingdom (UK)
Emergency telephone number : XXXX

2. Composition/information on ingredients

Substance/Preparation : Preparation

| Ingredient Name | CAS number | % | EC Number | Classification |
|--|------------|-------|-----------|--------------------|
| Europe | | | | |
| 2-(2-Butoxyethoxy)ethanol | 112-34-5 | 15-30 | 203-961-6 | Xi; R36 |
| Alcohols, C12-18, ethoxylated propoxylated. | 69227-21-0 | 5-15 | 500-242-1 | Xi; R38 |
| glycine, n,n-bis(carboxymethyl)-, trisodium salt | 5064-31-3 | 1-5 | 225-768-6 | Xn; R22 Xi; R36 |
| triethanolamine | 102-71-6 | 1-5 | 203-049-8 | |
| 1-Methoxy-2-propanol | 107-98-2 | 1-5 | 203-539-1 | R10 |
| See Section 16 for the full text of the R Phrases declared above | | | | |

* Occupational Exposure Limit(s), if available, are listed in Section 8

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi; R36
Human health hazards : Irritating to eyes.
Additional Hazards : Not applicable

See Section 11 for more detailed information on health effects and symptoms.

SAFETY DATA SHEET

Polish, wax and dirt remover

4. First aid measures

First aid measures

- Inhalation** : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention.
- Ingestion** : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.
- Skin Contact** : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Obtain medical attention.
- Eye contact** : In case of contact, immediately flush eyes with a copious amount of water for at least 15 minutes. Obtain medical attention immediately.

See Section 11 for more detailed information on health effects and symptoms.

5. Fire-fighting measures

- Extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical, or CQ.
- Special exposure hazards** : No specific hazard.
Not available.
- Hazardous thermal decomposition products** : These products are carbon oxides (CO, CO₂), nitrogen oxides (NO, NO₂...). Some metallic oxides.
- Special protective equipment for fire-fighters** : Fire-fighters should wear self-contained positive pressure breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

- Personal Precautions** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Follow all fire fighting procedures (Section 5).
- Environmental precautions and cleanup methods** : Minimize contact of spilled material with soils to prevent runoff to surface waterways. See Section 13 for Waste Disposal Information.
If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Note: See section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Avoid contact with eyes. Wash thoroughly after handling.
- Storage** : Keep container tightly closed. Keep container in a cool, well-ventilated area.
- Packaging materials**
- Recommended** : Use original container.
- Danish Fire Class** : Not available.
- Czech Republic - Storage Code** : III

SAFETY DATA SHEET

Polish, wax and dirt remover

8. Exposure controls/personal protection

| <u>Ingredient Name</u> | <u>Occupational Exposure Limits</u> |
|---------------------------|--|
| Europe | |
| triethanolamine | ACGIH TLV (United States, 2003). Notes: TWA: 5 mg/m ³ 8 hour(s). |
| 1-Methoxy-2-propanol | EU OEL (Europe, 2000). Skin Notes: Indicative STEL: 568 mg/m ³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 375 mg/m ³ 8 hour(s). TWA: 100 ppm 8 hour(s). |
| Sweden | |
| 2-(2-Butoxyethoxy)ethanol | AFS (Sweden, 2000). Notes: KTV: 200 mg/m ³ 15 minute(s). KTV: 30 ppm 15 minute(s). NGV: 100 mg/m ³ 8 hour(s). NGV: 15 ppm 8 hour(s). |
| triethanolamine | AFS (Sweden, 2000). Notes: KTV: 10 mg/m ³ 15 minute(s). NGV: 5 mg/m ³ 8 hour(s). |
| Denmark | |
| 2-(2-Butoxyethoxy)ethanol | Arbejdstilsynet (Denmark, 2002). Notes: GV: 100 mg/m ³ 8 hour(s). |
| triethanolamine | Arbejdstilsynet (Denmark, 2002). Notes: GV: 3,1 mg/m ³ 8 hour(s). GV: 0,5 ppm 8 hour(s). |
| 1-Methoxy-2-propanol | Arbejdstilsynet (Denmark, 2002). Notes: GV: 185 mg/m ³ 8 hour(s). GV: 50 ppm 8 hour(s). |
| Norway | |
| triethanolamine | Arbejdstilsynet (Norway, 2001). Notes: AN: 5 mg/m ³ 8 hour(s). |
| 1-Methoxy-2-propanol | Arbejdstilsynet (Norway, 2002). Skin Notes: AN: 180 mg/m ³ 8 hour(s). AN: 50 ppm 8 hour(s). |
| France | |
| 1-Methoxy-2-propanol | INRS (France, 1999). Notes: Advisory VME: 360 mg/m ³ 8 hour(s). VME: 100 ppm 8 hour(s). |
| Netherlands | |
| 2-(2-Butoxyethoxy)ethanol | Nationale MAC-lijst (Netherlands, 2003). Skin Notes: Legal TGG: 50 mg/m ³ 8 hour(s). TGG: 9 ppm 8 hour(s). |
| triethanolamine | Nationale MAC-lijst (Netherlands, 2003). Notes: Administrative TGG: 5 mg/m ³ 8 hour(s). |
| 1-Methoxy-2-propanol | Nationale MAC-lijst (Netherlands, 2003). Notes: Legal TGG: 375 mg/m ³ 8 hour(s). TGG: 100 ppm 8 hour(s). |
| Germany | |
| 2-(2-Butoxyethoxy)ethanol | MAK-Werte Liste (Germany, 2000). Notes: Spitzenbegrenzung: 100 mg/m ³ 15 minute(s). TWA: 100 mg/m ³ 8 hour(s). |
| triethanolamine | TRGS900 MAK (Germany, 2003). Notes: Spitzenbegrenzung: 100 mg/m ³ TWA: 100 mg/m ³ 8 hour(s). |
| | TRGS900 MAK (Germany, 2003). Notes: |

Date of issue

24-10-2003.

Version

5

Page: 3/11

SAFETY DATA SHEET

Polish, wax and dirt remover

| | |
|---|--|
| <p>1-Methoxy-2-propanol</p> | <p>TWA: 5 mg/m³ 8 hour(s). MAK-Werte Liste (Germany, 2000). Notes: Spitzenbegrenzung: 740 mg/m³ 15 minute(s). Spitzenbegrenzung: 200 ML/M3 15 minute(s). TWA: 370 mg/m³ 8 hour(s). TWA: 100 ML/M3 8 hour(s). TRGS900 MAK (Germany, 2003). Notes: Spitzenbegrenzung: 370 mg/m³ Spitzenbegrenzung: 100 ppm TWA: 370 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s).</p> |
| <p>Finland</p> <p>1-Methoxy-2-propanol</p> | <p>Työterveyslaitos (Finland, 2002). Notes: STEL: 560 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 370 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s).</p> |
| <p>United Kingdom (UK)</p> <p>1-Methoxy-2-propanol</p> | <p>EH40-OES (United Kingdom (UK), 2002). Skin Notes: STEL: 560 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 375 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s).</p> |
| <p>Austria</p> <p>2-(2-Butoxyethoxy)ethanol</p> <p>triethanolamine</p> <p>1-Methoxy-2-propanol</p> | <p>BMWA_MAK (Austria, 2003). Notes: Spitzenbegrenzung: 100 mg/m³ Spitzenbegrenzung: 15 ppm TWA: 100 mg/m³ 8 hour(s). TWA: 15 ppm 8 hour(s). BMWA_MAK (Austria, 2003). Notes: STEL: 10 mg/m³ 4 times per shift, 15 minute(s). Form: Aerosol STEL: 1,6 ppm 4 times per shift, 15 minute(s). Form: Aerosol TWA: 5 mg/m³ 8 hour(s). Form: Aerosol TWA: 0,8 ppm 8 hour(s). Form: Aerosol BMWA_MAK (Austria, 2003). Skin Notes: Spitzenbegrenzung: 187 mg/m³ Spitzenbegrenzung: 50 ppm TWA: 187 mg/m³ 8 hour(s). TWA: 50 ppm 8 hour(s).</p> |
| <p>Switzerland</p> <p>2-(2-Butoxyethoxy)ethanol</p> <p>1-Methoxy-2-propanol</p> | <p>SUVA (Switzerland, 2003). Notes: Kurzzeitgrenzwerte: 100 mg/m³ 15 minute(s). Form: Dust MAK: 100 mg/m³ 8 hour(s). Form: Dust SUVA (Switzerland, 2003). Notes: Kurzzeitgrenzwerte: 720 mg/m³ 15 minute(s). Kurzzeitgrenzwerte: 200 ppm 15 minute(s). MAK: 360 mg/m³ 8 hour(s). MAK: 100 ppm 8 hour(s).</p> |
| <p>Belgium</p> <p>triethanolamine</p> <p>1-Methoxy-2-propanol</p> | <p>Lijst Grenswaarden / Valeurs Limites (Belgium, 2002). Notes: VL: 5 mg/m³ 8 hour(s). Lijst Grenswaarden / Valeurs Limites (Belgium, 2002). Skin Notes: VCD: 568 mg/m³ 15 minute(s). VCD: 150 ppm 15 minute(s). VL: 375 mg/m³ 8 hour(s). VL: 100 ppm 8 hour(s).</p> |
| <p>Spain</p> | |

SAFETY DATA SHEET

Polish, wax and dirt remover

| | |
|---------------------------|--|
| 2-(2-Butoxyethoxy)ethanol | INSHT (Spain, 2003). Notes: TWA: 100 mg/m ³ 8 hour(s). |
| triethanolamine | INSHT (Spain, 2003). Notes: TWA: 5 mg/m ³ 8 hour(s). |
| 1-Methoxy-2-propanol | INSHT (Spain, 2003). Skin Notes: STEL: 568 mg/m ³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 375 mg/m ³ 8 hour(s). TWA: 100 ppm 8 hour(s). |
| Turkey | |
| Czech Republic | |
| 2-(2-Butoxyethoxy)ethanol | 178/2001 (Czech Republic, 2001). Notes: STEL: 200 mg/m ³ 10 minute(s). STEL: 30,2 ppm 10 minute(s). TWA: 100 mg/m ³ 8 hour(s). TWA: 15,1 ppm 8 hour(s). |
| triethanolamine | 178/2001 (Czech Republic, 2001). Notes: STEL: 10 mg/m ³ 10 minute(s). STEL: 1,64 ppm 10 minute(s). TWA: 5 mg/m ³ 8 hour(s). TWA: 0,82 ppm 8 hour(s). |
| 1-Methoxy-2-propanol | 178/2001 (Czech Republic, 2001). Skin Notes: STEL: 550 mg/m ³ 10 minute(s). STEL: 149,05 ppm 10 minute(s). TWA: 270 mg/m ³ 8 hour(s). TWA: 73,17 ppm 8 hour(s). |

Exposure controls

- Occupational exposure controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : A respirator is not needed under normal and intended conditions of product use.
- Hand protection** : Use latex gloves.
- Eye protection** : Safety glasses. Goggles, face shield, or other full-face protection if potential exists for direct exposure to aerosols or splashes.
- Skin protection** : Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits).
- Protection based on MAL** : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

General: Gloves must be worn for all work that may result in soiling. Apron/overalls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/overalls/protective clothing as appropriate or as instructed.

SAFETY DATA SHEET

Polish, wax and dirt remover

MAL-code: 0-3

Application: During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone.

- Overalls must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Arm protectors and apron must be worn.

During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Gas filter mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone; and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, overalls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

9. Physical and chemical properties

| | |
|---|---|
| General information | |
| Appearance | |
| Physical state | : Liquid. |
| Colour | : Clear Colourless. |
| Odour | : Characteristic. (Slight.) |
| Important health, safety and environmental information | |
| pH | : 12.8 [Basic.] |
| Melting point | : May start to solidify at 21°C (69.8°F) based on data for: triethanolamine. Weighted average: -16.11°C (3°F) |
| Boiling point | : The lowest known value is 72 to 77°C (161.6 to 170.6°F) (Alcohols, C12-18, ethoxylated propoxylated.). Weighted average: 134.91°C (274.8°F) |
| Flash point | : Closed cup: Higher than 93.3°C (200°F). |
| Flammability (solid, gas) | : Not applicable. |
| Explosive properties | : Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available. |
| Explosion Limits | : The greatest known range is LOWER: 1.9% UPPER: 13.1% (1-Methoxy-2-propanol) |
| Oxidising properties | : Not available. |
| Relative density | : 1.031 g/cm ³ |
| Solubility | : Easily soluble in cold water, hot water, methanol, diethyl ether, acetone. Insoluble in n-octanol. |

SAFETY DATA SHEET

Polish, wax and dirt remover

Viscosity : Dynamic: The highest known value is 135 cP (Alcohols, C12-18, ethoxylated propoxylated.)
Weighted average: 105.79 cP

Evaporation rate (butyl acetate = 1) : The highest known value is 0.814 (1-Methoxy-2-propanol) Weighted average: 0.27 compared to Butyl acetate.

Other information

Auto-ignition temperature : The lowest known value is >200°C (392°F) (Alcohols, C12-18, ethoxylated propoxylated.)

10. Stability and reactivity

Stability : The product is stable.

Conditions to Avoid : Not applicable

Hazardous Decomposition Products : These products are carbon oxides (CO, CO₂), nitrogen oxides (NO, NO₂...). Some metallic oxides.

11. Toxicological information

Potential Acute Health Effects

Inhalation : No specific hazard.

Ingestion : No specific hazard.

Skin Contact : No specific hazard.

Eye contact : Irritating to eyes.

Acute toxicity

| <u>Ingredient Name</u> | <u>Test</u> | <u>Result</u> | <u>Route</u> | <u>Species</u> |
|--|-------------------|------------------|--------------|----------------|
| 2-(2-Butoxyethoxy)ethanol | LD50 | 5660 mg/kg | Oral | Rat |
| | LD50 | 2200 mg/kg | Oral | Rabbit |
| | LD50 | 2400 mg/kg | Oral | Mouse |
| | LD50 | 2700 mg/kg | Dermal | Rabbit |
| Alcohols, C12-18, ethoxylated propoxylated. | LD50 | >2000 mg/kg | Oral | Rat |
| | | | | |
| glycine, n,n-bis(carboxymethyl)-, trisodium salt | LD50 | 1100 mg/kg | Oral | Rat |
| | LD50 | 681 mg/kg | Oral | Mouse |
| | LD50 | 750 mg/kg | Oral | Monkey |
| triethanolamine | LD50 | 5000 mg/kg | Oral | Rat |
| | LD50 | 5846 mg/kg | Oral | Mouse |
| | LD50 | 5846 mg/kg | Oral | Mouse |
| 1-Methoxy-2-propanol | LD50 | 10000 mg/kg | Dermal | Rabbit |
| | LD50 | 5000 mg/kg | Oral | Rat |
| | LD50 | 11700 mg/kg | Oral | Mouse |
| | LD50 | 13500 mg/kg | Dermal | Rabbit |
| | LDLo | >6 mg/kg | Oral | Rat |
| | LC50 | 7000 (6 hour(s)) | Inhalation | Rat |
| LC50 | 10000 (5 hour(s)) | Inhalation | Rat | |

Over-exposure signs/symptoms

Target Organs : Contains material which causes damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Other adverse effects : Not available.

SAFETY DATA SHEET

Polish, wax and dirt remover

12. Ecological information

Ecotoxicity Data

| <u>Ingredient Name</u> | <u>Species</u> | <u>Period</u> | <u>Result</u> |
|--|--------------------------------|---------------|---------------|
| 2-(2-Butoxyethoxy)ethanol | Lepomis macrochirus (LC50) | 96 hour(s) | 1300 mg/l |
| Alcohols, C12-18, ethoxylated propoxylated. | LEUCISCUS IDUS (LC50) | 96 hour(s) | 1 to 10 mg/l |
| glycine, n,n-bis(carboxymethyl)-, trisodium salt | Fish (LC50) | 96 hour(s) | >200 mg/l |
| triethanolamine | Scenedesmus subspicatus (EC50) | 72 hour(s) | 750 mg/l |
| | Scenedesmus subspicatus (EC50) | 48 hour(s) | 750 mg/l |
| | Pimephales promelas (LC50) | 96 hour(s) | 11800 mg/l |
| 1-Methoxy-2-propanol | Bacteria (EC50) | 48 hour(s) | >1000 mg/l |
| | Fish (LC50) | 96 hour(s) | >1000 mg/l |

Other Ecological Information

| <u>Ingredient Name</u> | <u>Persistence/degradability</u> | | | | | | <u>Bioaccumulative potential</u> | | |
|---|----------------------------------|-----|------|-------------------|------------|------------------------|----------------------------------|-----|-----------|
| | BOD ₅ | COD | ThOD | Aquatic Half-life | Photolysis | Biodegradability | LogP _{ow} | BCF | Potential |
| triethanolamine 1-Methoxy-2-propanol | | | | | | Not readily Readily | <1 | | low |

Mobility : Not available.

Other adverse effects : Not available.

13. Disposal considerations

Methods of disposal : Avoid contact of spilled material and runoff with soil and surface waterways. Dispose of according to all federal, state and local applicable regulations.

Waste Classification : Not applicable.

European Waste Catalogue (EWC) : Not available.

Hazardous Waste : The classification of the product may meet the criteria for a hazardous waste

14. Transport information

International transport regulations

| Regulatory information | UN number | Proper shipping name | Class | Packing group | Label | Additional Information |
|------------------------|----------------|----------------------|-------|---------------|-------|------------------------|
| ADR/RID Class | Not regulated. | - | - | - | | - |
| ADN Class | Not regulated. | - | - | - | | - |
| IMDG Class | Not regulated. | - | - | - | | - |
| IATA-DGR Class | Not regulated. | - | - | - | | - |

Date of issue

24-10-2003.

Version

5


Page: 8/11

SAFETY DATA SHEET

Polish, wax and dirt remover

15. Regulatory information


EU Regulations

- Hazard symbol(s)** : 
Irritant
- Risk phrases** : R36- Irritating to eyes.
- Safety Phrases** : S2- Keep out of the reach of children.
S25- Avoid contact with eyes.
S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S46- If swallowed, seek medical advice immediately and show this container or label.
S64- If swallowed, rinse mouth with water (only if the person is conscious).
- Product Use** : Classification and labelling have been performed according to EU directives 67/548/EEC, 1999/45/EC, including amendments and the intended use.
- Consumer applications.
- EC Statistical Classification (Tariff Code)** : 32089091


National regulations

Sweden

Denmark

- Hazard symbol(s)** : 
Irritant
- Risk Phrases** : R36- Irritating to eyes.
- Safety Phrases** : S2- Keep out of the reach of children.
S25- Avoid contact with eyes.
S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S46- If swallowed, seek medical advice immediately and show this container or label.
S64- If swallowed, rinse mouth with water (only if the person is conscious).
- MAL-code** : 0-3
- Denmark – Restrictions on Use** : Not to be used by professional users below 18 years of age, see the National Working Environment Authorities Executive Order on young peoples dangerous work.
- Statutory Order 571 on Aerosols** : Not applicable.

Norway

- Hazard symbol(s)** : 
Irritant
- Risk Phrases** : R36- Irritating to eyes.

SAFETY DATA SHEET

Polish, wax and dirt remover

Safety Phrases : S2- Keep out of the reach of children.
 S25- Avoid contact with eyes.
 S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S46- If swallowed, seek medical advice immediately and show this container or label.
 S64- If swallowed, rinse mouth with water (only if the person is conscious).

Carcinogenic Class : Not classified.

France

Netherlands

Germany

Employment restrictions in accordance with § 15b of the Hazardous Substance Ordinance : Yes.

Hazardous Incident Ordinance : No.

Ordinance on Combustible Liquids : Class: Omitted

Hazard class for water : 3

Austria



Limitation of the Use of Organic Solvents : Permitted.

Italy

Restrictions on the use of Benzol and Similar materials : Not applicable.

Emissions Control Directive : 100% Not classified.

16. Other information

Full text of R phrases referred to in Sections 2 and 3 - Europe : R10- Flammable.
 R22- Harmful if swallowed.
 R36- Irritating to eyes.
 R38- Irritating to skin.

Full text of classifications referred to in Sections 2 and 3 - Europe : Xn - Harmful
 Xi - Irritant

Full text of R phrases referred to in Sections 2 and 3 - Switzerland : R10- Flammable.
 R22- Harmful if swallowed.
 R36- Irritating to eyes.
 R38- Irritating to skin.

Full text of classifications referred to in Sections 2 and 3 - Switzerland : Xn - Harmful
 Xi - Irritant

Full text of R phrases referred to in Sections 2 and 3 - Turkey : R22- Harmful if swallowed.
 R36- Irritating to eyes.
 R38- Irritating to skin.

SAFETY DATA SHEET

Polish, wax and dirt remover

Full text of classifications referred to in Sections 2 and 3 - Turkey : Xn - Harmful
Xi - Irritant

Full text of R phrases referred to in Sections 2 and 3 - Czech Republic : R10- Flammable.
R22- Harmful if swallowed.
R36- Irritating to eyes.
R38- Irritating to skin.

Full text of classifications referred to in Sections 2 and 3 - Czech Republic : Xn - Harmful
Xi - Irritant

HISTORY

Date of printing : 24-10-2003.
Date of issue : 24-10-2003.
Date of previous issue : No Previous Validation.
Version : 5
Verified by T. Rutgers.

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

| | |
|---------|---|
| Version | 5 |
|---------|---|

| |
|-------------|
| Page: 11/11 |
|-------------|