












# POLISHED PORCELAIN WALL TILE

## FEATURES AND BENEFITS

-  Please check that the wall is strong enough to take the extra load.
-  Please ensure that all tiles are sealed using porcelain impregnator/sealer before fixing.
-  Please then ensure that after fixing, tiles are completely cleaned and then re-apply porcelain impregnator/sealer before grouting. Always follow manufacturers instructions.

-  Create the look of real stone with easy care polished porcelain
-  Durable and hardwearing
-  Easy to clean

This product can be used in the following areas:

-  Lounge/Dining areas
-  Kitchens and Utility rooms
-  Hallways and Porches
-  Bathrooms and cloakrooms
-  Conservatories and outdoors

## POLISHED PORCELAIN WALL TILE FIXING INSTRUCTIONS

### 1. Prepare

Ensure that the surface is sound, dry, flat and free from dirt grease or flaking.

### 2. Plan

Arrange tiles in the desired layout before fixing. Mix the contents of two or three packs of tiles to achieve an acceptable blend of colour and shade. For external edges, an edging strip is available.

### 3. Fixing

Using an adhesive trowel, apply the tile adhesive, following the adhesive manufacturer's instructions.

Place the first tile on a straight line. A spirit level will be helpful.

Press tiles firmly into position, fixing all full tiles first. Use tile spacers to form even gaps.

Remove all excess adhesive from the surface of the tile before it dries.

### 4. Sealing

Thoroughly clean and dry the tiles and then apply impregnator/sealer before grouting.

Following the sealer manufacturer's instructions.

### 5. Cutting

Tiles can be cut to size using a wet or dry tile cutter.

### 6. Grouting

Do not use highly pigmented e.g black, blue, green grouts on these tiles. Test that the grout used will not stain the tile.

Allow 12 hours for the tile adhesive to set before grouting.

Use the grout float to grout well into the tile joints and remove any excess immediately with a damp sponge.

Allow to dry before applying a second coat of sealer.

Always follow the grout manufacturer's instructions. Use a grout finisher to obtain a professional result. When the grout is fully dry, wipe over with a clean dry cloth.