










GLAZED CERAMIC WALL TILE

FEATURES AND BENEFITS

-  Please check that the wall is strong enough to take the extra load
-  Great looking wall spaces with easy care ceramic
-  Durable and hardwearing
-  Easy to clean

This product can be used in the following areas:

-  Lounge/Dining areas
-  Kitchens and Utility rooms
-  Hallways and Porches
-  Bathrooms
-  Conservatories

GLAZED CERAMIC WALL TILE FIXING INSTRUCTIONS

1. Prepare

Ensure that the surface is sound, dry, flat and free from dirt grease or flaking.

2. Plan

Arrange tiles in the desired layout before fixing. Mix the contents of two or three packs of tiles to achieve an acceptable blend of colour and shade. For external edges, an edging strip is available.

3. Fixing

Using an adhesive trowel, apply the tile adhesive, following the adhesive manufacturer's instructions.

Place the first tile on a straight line. A spirit level will be helpful.

Press tiles firmly into position, fixing all full tiles first. Use tile spacers to form even gaps.

Remove all excess adhesive from the surface of the tile before it dries.

4. Cutting

Tiles can be cut to size using a wet or dry tile cutter.

5. Grouting

Allow 12 hours for the tile adhesive to set before grouting. Use the grout float to grout well into the tile joints and remove any excess immediately with a damp sponge. Allow to dry before applying a second coat of sealer.

Always follow the grout manufacturer's instructions.

Use a grout finisher to obtain a professional result. When the grout is fully dry, wipe over with a clean dry cloth.