











QUARRY FLOOR TILE

FEATURES AND BENEFITS

-  Please check that the floor is strong enough to take the extra load
-  Natural clay gives an authentic and quality finish
-  Durable and hardwearing
-  Easy to clean
-  Suitable for interior or exterior use

This product can be used in the following areas:

-  Lounge/Dining areas
-  Kitchens and Utility rooms
-  Hallways and Porches
-  Bathrooms
-  Conservatories and Patios

QUARRY FLOOR TILE FIXING INSTRUCTIONS

1. Prepare

Ensure that the surface is sound, dry, flat and free from dirt grease or flaking.

2. Plan

Arrange tiles in the desired layout before fixing. Mix the contents of two or three packs of tiles to achieve an acceptable blend of colour and shade. For external edges, an edging strip is available.

3. Fixing

Using an adhesive trowel, apply the tile adhesive, following the adhesive manufacturer's instructions.

Place the first tile on a straight line. A spirit level will be helpful.

Press tiles firmly into position, fixing all full tiles first. Ensure all underside fixing ribs face the same direction and a MINIMUM 6mm grout spacing between tiles.

Remove all excess adhesive from the surface of the tile before it dries.

4. Cutting

Tiles can be cut to size using a wet or dry tile cutter.

5. Grouting

Allow 12 hours for the tile adhesive to set before grouting. Use the grout float to grout well into the tile joints and remove any excess immediately with a damp sponge. Always follow the grout manufacturer's instructions.

Use a grout finisher to obtain a professional result. When grout is set thoroughly clean the tile surfaces with a suitable post-fix cleaner and rinse with clean water.